

Sieve Cleaning Balls



Natural Rubber



Silica Gel



PU

Comparison of Performance Parameters (NB, SILICON, PU)

	Natural Rubber	Silica Gel	PU
Hardness (Shore A)	55-85	55-85	70-85
Working Temperature °C	-25~+100	0~+220	-40~+120
Oil Resistance	Ordinary	Ordinary	Good
Bounce	Good	Ordinary	Ordinary+
Abrasion Resistance	Ordinary+	Good	Excellent
Rebound Rate	≥75%	/	/

Common specifications (Material: Rubber, Silica Gel, PU)

Diameter Φ mm	Quantity of Carton	Weight of Carton Kg	Size of Carton cm	Volume of Carton M ³
12	6000	7.8	32x32x32	0.017
16	3000	8.1	32x32x32	0.017
19	2000	9.2	32x32x32	0.017
22	1500	10.8	30*25*22	0.017
24	1000	9.4	30*25*22	0.017
26	1500	18.0	32x32x32	0.033
28	1200	18.0	32x32x32	0.033
30	1000	18.5	32x32x32	0.033
32	800	18.0	32x32x32	0.033
35	600	18.0	32x32x32	0.033
38	500	19.2	50X40X23	0.035
40	400	17.6	50X40X23	0.035
45	300	18.8	50X40X23	0.035
50	200	17.3	50X40X23	0.035
55	150	17.3	50X40X23	0.035
60	100	14.9	50X40X23	0.035